DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Reference number of the declaration of performance:	IN 5542005	
Unique identification code of the product-type:	MC-Injekt GL-95 TX (P)	
Intended use:	Concrete injection for swelling fitted filling of cracks, voids and interstices (S) U (S2) W (1) (2/3/4) (1/40)	
Manufacturer:	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop	
System of AVCP:	System 2+ (for uses in buildings and civil engineering works)	
Harmonised standard:	EN 1504-5:2004	
Notified body:	Karlsruher Institut für Technologie (KIT), 0754-CPR-15-0412	

Declared performances:


Essential characteristics	Performance	Harmonised technical specification
Water tightness	S2	
Workability	< 60 mPa·s	
Corrosion behaviour	It is assumed that no corrosive effects are present	
Expansion ratio and evolution by water storage	40 %	EN 1504-5:2004
Volume- and weight changes by air drying and water storage	NPD	
Durability: Sensitivity to water	Fulfilled	
Durability: Sensitivity to wetdrying cycles	Fulfilled	
Durability: Compatibility with concrete	Fulfilled	
Release of dangerous substances	EN 1504-5, Art. 5.4	

a) Pursuant to Commission Decision 2010/85 / EU of 09.02.2010, the product complies with fire classification E, without that an examination is required.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of research and development and quality control



Bottrop, 15.05.2019 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.