## **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Reference number of the declaration of performance:

IN4004001

Unique identification code of the product-type: Nafufill R3 FM

Intended use:

Product for structural and non-structural repair for concrete

Applying mortar by hand (3.1) Spraying concrete or mortar (3.3)

Manufacturer:

MC-Bauchemie Müller GmbH & Co.KG

Am Kruppwald 1-8 46238 Bottrop

**System of AVCP:** 

System 2+ (for uses in buildings and civil engineering works)

Harmonised standard:

EN 1504-3:2005

**Notified body:** 

Institut für Massivbau und Baustofftechnologie

Universität Karlsruhe (TH) Identification no: 0754

## **Declared performances:**

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Compressive strength	class R3		
Chloride ion content	≤ 0.05 %		
Adhesive bond	≥ 1.5 MPa		
Restrained shrinkage/expansion	≥ 1.5 MPa	System 2+	EN 1504-3:2005
Thermal compatibility Freeze-thaw	≥ 1.5 MPa		
Thermal compatibily	≥ 1.5 MPa		
Capillary absorption	0.32 kg x m² x h <sup>0.5</sup>		
Carbonation resistance	passed		
Reaction to fire	class A2-s1,d0		
Dangerous substances	EN 1504-3 Pkt. 5.4		

7

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



(signature)

## John van Diemen Head of research and development and quality control

Bottrop, 21.11.2019 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH),

Annex II is attached to this Declaration of Performance.